

NOTES:

- TYPICAL TREE WELL SIZE IS 8' LONG BY 4' WIDE, OR AS DIRECTED BY CITY.
 DIG PLANTING PIT TO FIT PLANTER. DIG NO DEEPER THAN THE DEPTH OF THE ROOTBALL.
 SET ROOTBALL ON FIRM SURFACE. PLACE ROOT FLARE SLIGHTLY BELOW SIDEWALK GRADE TO ALLOW FOR TOP OF MULCH AT SIDEWALK
- 4. BACKFILL WITH TOPSOIL.
- MULCH WITH BARK TO A MIN. DEPTH OF 2". KEEP MULCH 6" AWAY FROM TRUNK. IF GRATE IS REQUIRED, TOP OF MULCH IS TO BE 3"
- LOWER THAN SURFACE OF SIDEWALK.

 6. ON BALLED AND BURLAP TREES, CUT & PEEL AWAY WIRE FRAME FROM ROOTBALL, LEAVE BURLAP AND FRAME IN PLANTING HOLE.

 7. A ROOT CONTROL SYSTEM, BIOBARRIER, DEEPROOT, OR APPROVED EQUAL, SHALL BE INSTALLED ON ALL SIDES ADJACENT TO HARDSCAPE. IT SHALL BE INSTALLED VERTICALLY A MINIMUM OF 18" IN DEPTH FROM FINISH GRADE AND PER MANUFACTURER'S RECOMMENDATIONS.

 8. INSTALL TWO (2) 4" X 36" PERFORATED PLASTIC DEEP WATERING TUBES ON EITHER SIDE OF TREE.



MCMINNVILLE PUBLIC WORKS STREET TREE PLANTING DETAIL-TREE WELLS

NOT TO SCALE

DRAWN BY:

MB

AUGUST 2025

DRAWING NO.

34A